

2-post lifts ATH Comfort Lift




**Innovative
ATH-FREE-LINE system**

Fast – Easy – Efficient

**Fast lifting and
lowering**




Secondary control panel on second column



Three-part telescopic lifting arms with double-telescopic lifting plates and twist protection



"Energy-Set" (230V / 12V / compressed air jack)



Drive over plate with very low drive over height of 20 mm

ATH Comfort Lift

Our new 2-post lifts

ATH Lifting Technology

2-post lifts ATH Comfort Lift



ATH Comfort Lift

- High-quality and rugged electro-hydraulic 2-post lift with a fully automatic electric system
- **FREE-LINE concept at 3,2 and 4 t lifts:** With optional accessories upgradable on each 3,2 and 4 t lifts
- Choices between **three different models**
 - **ATH Comfort:** Very low drive over plate (height = 20 mm) to protect hydraulic hoses and synchronization ropes
 - **ATH Comfort (L-model):** Lightweight construction for easy and safe installation; synchronization ropes and hydraulic hose are installed in the cross beam
 - **ATH Comfort (X-model):** Extra large post extension for high vehicles with cross beam, synchronization ropes and hydraulic hose are installed in the cross beam
- Multifunctional operating range by **three-part telescopic lifting arms** optionally in **asymmetric (short–long) version** or in **symmetric (long–long) version**, each with **double-telescopic lifting plates** and **twist protection**
- **Asymmetric lifting arms (short - long) or symmetric lifting arms (long - long) optionally available as an accessory**
- Automatically unlocking of lifting arm blocking
- **Secondary control panel and built in "Energy-Set"** (consisting of 230V plug/ 12V plug/ compressed air jack) available on all ATH 2-post lifts
- Warp-resistant construction with high precise laser cut manufacturing and robotic welding
- Lifting height of all lifts: 2000 mm
- Double safety through built-in safety locks and compensating wire ropes
- Electromagnetic safety locking system
- Trouble-free and secure synchronization with 10 mm pull ropes
- High hydraulic power unit for fast lifting and lowering
- Band-cover for protection of cylinders, chains and ropes included



ATH Comfort Lift



ATH Comfort Lift
(L-model)



ATH Comfort Lift
(X-model)

Type	FREE-LINE									STRONG-LINE	
	Comfort 2.30	Comfort 2.30L	Comfort 2.30X	Comfort 2.35	Comfort 2.35L	Comfort 2.35X	Comfort 2.40	Comfort 2.40L	Comfort 2.40X	Comfort 2.50	Comfort 2.50X
Load capacity kg	3.000	3.000	3.000	3.500	3.500	3.500	4.000	4.000	4.000	5.000	5.000
Lifting height mm	2.000	2.000	2.000	2.000	2.000	2.000	2.000	2.000	2.000	2.000	2.000
Total height mm	3.140	4.000	4.900	3.140	4.000	4.900	3.140	4.000	4.900	3.140	5.000
Drive-through height mm	---	3.680	4.580	---	3.680	4.580	---	3.680	4.580	---	4.580
Total width mm	3.520	3.520	3.520	3.520	3.520	3.520	3.520	3.520	3.520	4.050	4.050
Drive-through width mm	2.510	2.510	2.510	2.510	2.510	2.510	2.510	2.510	2.510	3.030	3.030
Lifting- / lowering time sec	30/32	30/32	30/32	32/32	32/32	32/32	35/32	35/32	35/32	45/35	45/38
Driving power kW	3,0	3,0	3,0	3,0	3,0	3,0	3,0	3,0	3,0	3,0	3,0
Drive over plate mm	20	---	---	20	---	---	20	---	---	20	---
Suitable for high vehicles	X		X	X		X	X		X	X	X